


LED Industrieleuchte  
 LED industrial luminaire

 INROLED\_50 Ecolab ECO, 1065 mm, 24V DC  
 temperaturbeständig

Artikel-Nr.: 110210-02  
 EAN: 4260556624952

Bestell-Nr.:	110210-02
Modell:	INROLED_50
Bauform:	LED Rohrleuchte
Leuchtmittel:	SMD LED
Lampenleistung:	~24 W
Lampenlichtstrom:	3780 lm
Lampenlichtausbeute:	145 lm/W
Lichtverteilung:	direkt
Lichtfarbe:	Tageslichtweiß (5200 - 5700K)
Anschlusswert Leuchte:	24V DC $\pm$ 10%
Anschluss Leuchte:	M12 A-kodiert
Schutzart:	IP67/IP69K
Schutzklasse:	III
Entblendung:	opalweiß
Abstrahlwinkel:	100°
Betriebstemperatur:	-30... +65 °C (kurzzeitig +70°C)
Farbwiedergabe (Ra):	> 85
Lampenlebensdauer:	> 60.000 h
Schlagfestigkeit:	IK09
Material Abdeckung:	Polycarbonat, matt, splitterfrei mit Ecolab-Beschichtung
Höhe [B] x Breite [C]:	$\varnothing$ 50 mm
Länge [A]:	1065 mm
Gewicht:	1650 g
Bruttogewicht:	1950 g
Risikogruppe:	freie Gruppe
Befestigungszubehör:	Leuchtenhalter aus metalldektierbaren PP inklusive
Dimmbar:	optional über Zubehör
Kennzeichnung:	CE, ETL Listed
Gefertigt in:	Deutschland
Besonderheit:	Food+Beverage geeignet: Ecolab zertifiziert, HACCP-Zertifikat





## INROLED\_50 Ecolab ECO, 1065 mm, 24V DC temperature-resistant

**Item number:** 110210-02  
**EAN:** 4260556624952

<b>Order number:</b>	110210-02
<b>Model:</b>	INROLED_50
<b>Type:</b>	LED tube luminaire
<b>Illuminant:</b>	SMD LED
<b>Power consumption:</b>	~24 W
<b>Lamp luminous flux:</b>	3780 lm
<b>Lamp luminous efficiency:</b>	145 lm/W
<b>Light distribution:</b>	direct
<b>Light colour:</b>	daylight white (5200 - 5700K)
<b>Connected load:</b>	24V DC $\pm$ 10%
<b>Connection (connector):</b>	M12 connector A-type encoded
<b>Degree of protection:</b>	IP67/IP69K
<b>Class of protection:</b>	III
<b>Glare-free</b>	opal white
<b>Beam angle (optics):</b>	100°
<b>Operating temperature:</b>	-30... +65 °C (temporary +70°C)
<b>Colour rendering (Ra):</b>	> 85
<b>Lamps lifetime:</b>	> 60,000 h
<b>Impact-resistant:</b>	IK09
<b>Cover material:</b>	polycarbonate, milky, shatterproof with Ecolab coating
<b>Height [B] x Width [C]:</b>	Ø 50 mm
<b>Length [A]:</b>	1065 mm
<b>Weight (net):</b>	1650 g
<b>Gross weight:</b>	1950 g
<b>Risk group (DIN EN 62471):</b>	free group
<b>Mounting accessories:</b>	incl. luminaire holder made of metal detectable PP
<b>Dimmable:</b>	via optional accessory
<b>Marking:</b>	CE, ETL Listed
<b>Made in:</b>	Germany
<b>Feature:</b>	Food+Beverage suitable: Ecolab certified, HACCP certificate

