


LED Industrieleuchte  
 LED industrial luminaire

 INROLED\_50 Ecolab ECO, 305 mm, 24V DC  
 temperaturbeständig

**Artikel-Nr.:** 110010-02  
**EAN:** 94260556624938

<b>Bestell-Nr.:</b>	110010-02
<b>Modell:</b>	INROLED_50
<b>Bauform:</b>	LED Rohrleuchte
<b>Leuchtmittel:</b>	SMD LED
<b>Lampenleistung:</b>	~6 W
<b>Lampenlichtstrom:</b>	945 lm
<b>Lampenlichtausbeute:</b>	145 lm/W
<b>Lichtverteilung:</b>	direkt
<b>Lichtfarbe:</b>	Tageslichtweiß (5200 - 5700K)
<b>Anschlusswert Leuchte:</b>	24V DC ± 10%
<b>Anschluss Leuchte:</b>	M12 A-kodiert
<b>Schutzart:</b>	IP67/IP69K
<b>Schutzklasse:</b>	III
<b>Entblendung:</b>	opalweiß
<b>Abstrahlwinkel:</b>	100°
<b>Betriebstemperatur:</b>	-30... +65 °C (kurzzeitig +70°C)
<b>Farbwiedergabe (Ra):</b>	> 85
<b>Lampenlebensdauer:</b>	> 60.000 h
<b>Schlagfestigkeit:</b>	IK09
<b>Material Abdeckung:</b>	Polycarbonat, matt, splitterfrei mit Ecolab-Beschichtung
<b>Höhe [B] x Breite [C]:</b>	Ø 50 mm
<b>Länge [A]:</b>	305 mm
<b>Gewicht:</b>	450 g
<b>Bruttogewicht:</b>	650 g
<b>Risikogruppe:</b>	freie Gruppe
<b>Befestigungszubehör:</b>	Leuchtenhalter aus metalldektierbaren PP inklusive
<b>Dimmbar:</b>	optional über Zubehör
<b>Kennzeichnung:</b>	CE, ETL Listed
<b>Gefertigt in:</b>	Deutschland
<b>Besonderheit:</b>	Food+Beverage geeignet: Ecolab zertifiziert, HACCP-Zertifikat





## INROLED\_50 Ecolab ECO, 305 mm, 24V DC temperature-resistant

**Item number:** 110010-02  
**EAN:** 94260556624938

<b>Order number:</b>	110010-02
<b>Model:</b>	INROLED_50
<b>Type:</b>	LED tube luminaire
<b>Illuminant:</b>	SMD LED
<b>Power consumption:</b>	~6 W
<b>Lamp luminous flux:</b>	945 lm
<b>Lamp luminous efficiency:</b>	145 lm/W
<b>Light distribution:</b>	direct
<b>Light colour:</b>	daylight white (5200 - 5700K)
<b>Connected load:</b>	24V DC ± 10%
<b>Connection (connector):</b>	M12 connector A-type encoded
<b>Degree of protection:</b>	IP67/IP69K
<b>Class of protection:</b>	III
<b>Glare-free</b>	opal white
<b>Beam angle (optics):</b>	100°
<b>Operating temperature:</b>	-30... +65 °C (temporary +70°C)
<b>Colour rendering (Ra):</b>	> 85
<b>Lamps lifetime:</b>	> 60,000 h
<b>Impact-resistant:</b>	IK09
<b>Cover material:</b>	polycarbonate, milky, shatterproof with Ecolab coating
<b>Height [B] x Width [C]:</b>	Ø 50 mm
<b>Length [A]:</b>	305 mm
<b>Weight (net):</b>	450 g
<b>Gross weight:</b>	650 g
<b>Risk group (DIN EN 62471):</b>	free group
<b>Mounting accessories:</b>	incl. luminaire holder made of metal detectable PP
<b>Dimmable:</b>	via optional accessory
<b>Marking:</b>	CE, ETL Listed
<b>Made in:</b>	Germany
<b>Feature:</b>	Food+Beverage suitable: Ecolab certified, HACCP certificate

