

## LED Arbeitsplatzleuchte



### LED workplace luminaire



## UNILED II Gelenkarm, dimmbar, 5200-5700K, Leuchtenbreite 298 mm

**Artikelnr.:** 120610-02  
**EAN:** 4260556620268

<b>Bestell-Nr.:</b>	120610-02
<b>Modell:</b>	UNILED II Gelenkarm
<b>Bauform:</b>	LED Gelenkarmleuchte
<b>Leuchtmittel:</b>	SMD LED
<b>Lampenleistung:</b>	~14 W
<b>Lampenlichtstrom:</b>	1617 lm
<b>Lampenlichtausbeute:</b>	ca. 131 lm/W
<b>Lichtverteilung:</b>	direkt
<b>Lichtfarbe:</b>	Tageslichtweiß (5200 - 5700K)
<b>Anschlusswert Leuchte:</b>	24V DC ± 10%
<b>Betriebsgerät:</b>	Netzteil 110-240V AC inkl.
<b>Anschluss Leuchte:</b>	M12 Sensorstecker A-kodiert
<b>Anschlusswert Netzteil:</b>	100-240V AC
<b>Anschluss Netzteil:</b>	EURO Stecker zu M12 Steckverbinder
<b>Schutzart:</b>	IP40
<b>Schutzklasse:</b>	III
<b>Entblendung:</b>	opalweiß
<b>Abstrahlwinkel:</b>	100°
<b>Betriebstemperatur:</b>	-10... +60 °C
<b>Farbwiedergabe (Ra):</b>	> 85
<b>Lampenlebensdauer:</b>	> 60.000 h
<b>Material Gehäuse:</b>	Aluminium / Kunststoff
<b>Material Abdeckung:</b>	Makrolon
<b>Länge Kopf [A]:</b>	298 mm
<b>Länge Gelenkarme:</b>	2x 400 mm
<b>Gewicht:</b>	1900 g
<b>Bruttogewicht:</b>	3550 g
<b>Risikogruppe:</b>	freie Gruppe
<b>Befestigungszubehör:</b>	Tischklemme inkl.
<b>Dimmbar:</b>	Dimmer mit Memory Funktion intern
<b>Gefertigt in:</b>	Deutschland
<b>Besonderheit:</b>	dimmbar, schmale Leuchtenbreite



LED Arbeitsplatzleuchte  
LED workplace luminaire



**UNILED II Gelenkarm (adjustable arm), dimmable, 5200-5700K, luminaire head width 298 mm**

**Item number:** 120610-02  
**EAN:** 4260556620268

<b>Order number:</b>	120610-02
<b>Model:</b>	UNILED II Gelenkarm (adjustable arm)
<b>Type:</b>	LED adjustable arm luminaire
<b>Illuminant:</b>	SMD LED
<b>Power consumption:</b>	~14 W
<b>Lamp luminous flux:</b>	1617 lm
<b>Lamp luminous efficiency:</b>	ca. 131 lm/W
<b>Light distribution:</b>	direct
<b>Light colour:</b>	daylight white (5200 - 5700K)
<b>Connected load:</b>	24V DC $\pm$ 10%
<b>Power supply:</b>	included external PSU 100-240V AC
<b>Connection (connector):</b>	M12 A-type encoded
<b>Connected load PSU:</b>	100-240V AC
<b>Connection PSU:</b>	EURO plug to connector M12
<b>Degree of protection:</b>	IP40
<b>Class of protection:</b>	III
<b>Glare-free</b>	opal white
<b>Beam angle (optics):</b>	100°
<b>Operating temperature:</b>	-10... +60 °C
<b>Colour rendering (Ra):</b>	> 85
<b>Lamps lifetime:</b>	> 60,000 h
<b>Housing material:</b>	aluminium / plastics
<b>Cover material:</b>	Makrolon®
<b>Head width [A]:</b>	298 mm
<b>Length adjustable arms:</b>	2x 400 mm
<b>Weight (net):</b>	1900 g
<b>Gross weight:</b>	3550 g
<b>Risk group (DIN EN 62471):</b>	free group
<b>Mounting accessories:</b>	included table clamp
<b>Dimmable:</b>	internal dimmer with memory function
<b>Made in:</b>	Germany
<b>Feature:</b>	dimmable, short luminaire head

