

New

Dynamic Indication, Greater Control



Multi-color Model

Mono-color Model (Red)

Compact and Efficient

- Touch sensor enables real-time status confirmations.
- Features simultaneous use of continuous, flashing, and audible alarm conditions.
- Newly developed reflector emits evenly distributed light, preventing ambiguous indication
- High protection rating for operation in harsh environments


Identify and Resolve Issues Quickly



Notify when tasks are completed



Call for manager or parts



Signal equipment statuses



Built-in capacitive touch sensor.

- Up to 7 selectable colors
- Able to choose between 4 patterns (red, blue, white, or off) when engaging touch sensor
- Touch sensor is able to detect bare or gloved hands and even when wet
- Ability to choose 2 touch settings: light on only while sensor is being touched, or touch to activate/deactivate continuous light
- Audible alarm can be sounded in combination with continuous/flashing light and touch sensor



The Red, Green and Blue wires achieve 7 colors

Specifications

| Model | NE-24A-□ □ : R/Y/G/B/C | NE-M1ANN-M | NE-M1ANB-M | NE-M1ATB-M |
|-------------------------|------------------------------------|--|------------------------------------|---------------------------|
| Dimensions | Φ56mm | | | |
| Operating Voltages | 24V DC | 12-24V DC | | |
| Mounting location | Indoor | | | |
| mounting direction | all directions | | | |
| Protection Rating | IP65 NEMA TYPE 4X, 13 | IP67 NEMA TYPE 4X, 13 | IP65 / NEMA TYPE 4X, 13 | |
| Light Color | Red / Amber / Green / Blue / White | Multi-color (Red Amber Green Blue White Cyan Purple) | | |
| Sound Pressure | - | | 88dB Intermittent or Continuous | |
| Operation Specification | Continuous | Continuous / Flashing | | Continuous / Touch sensor |
| Wiring | Screwless terminal block | Cabtire cable (2m) | | |

Options

Upper Bracket NE-001D



Wall Mount Bracket NE-002D



1/2" NPT Bracket SZP-092D



Model Code

Monochromatic model

NE-24A-□

Operating Voltages

24 : 24V DC

Light color

R : Red Y : Amber
G : Green B : Blue
C : Clear

Multi-color model

NE-M1ATB-M
NE-M1ANB-M
NE-M1ANN-M

Operating Voltages

M1 : 12~24V DC

Touch sensor

T : With Touch Sensor
N : No Touch Sensor

Light color

M : Multi-color

Buzzer

B : With Buzzer
N : No Buzzer

*Download the instruction manual from our website (www.patlite.com) for additional details on wiring and dimensions.